

Hi-Temp Multipurpose Grease #2

Product Description

Relyant® Hi-Temp Multipurpose Grease #2 is a lithium complex grease intended for a wide range of applications and severe operating conditions. It is fortified with extreme-pressure additives along with rust and oxidation inhibitors, ensuring dependable performance in demanding environments. The lithium complex thickener system provides excellent high-temperature capability, strong adhesion, outstanding structural stability, and resistance to water contamination. Its chemically stable formulation delivers reliable protection against rust, corrosion, and wear. This product meets or exceeds NLGI GC-LB performance requirements.

Applications

Relyant® Hi-Temp Multipurpose Grease #2 is designed for a wide range of applications, including heavy-duty over-the-road trucks, automotive chassis lubrication, ball joints, universal joints, kingpins, and bushings. It is also suitable for use for general agricultural equipment, light industrial lubrication, light off-highway machinery, wheel bearings (disc and drum), and fifth-wheel protection.

Typical Properties

Description	Test Method
NLGI consistency number	2
Color	Red
Texture	Smooth, Tacky
Thickener Type	Lithium Complex
Base oil Viscosity, cSt	
@ 40°C	220
@ 100°C	15
Dropping Point, °C	>260°C
Four Ball Weld, Kg	315

* The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.