



Relyant[®]

SPECIAL HD Gas Engine Oil 15W-40 MULTIGRADE HEAVY-DUTY MOTOR OIL

	<u>Typical Properties</u>
SAE Grade, Automotive	15W-40
Viscosity, cSt	
At 40° C	113
At 100° C	15.2
Viscosity, SUS	
At 100° F	581
At 210° F	80
Viscosity Index	140
Viscosity, CCS, D-5293, -20° C/cP	6600
Flash Point, (COC), °F	420
Pour Point, °F	-25
Sulfated Ash, %wt	0.50
Neutralization No., TBN-E	5.0
Gravity, API @ 60° F	28.0

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

A premium-quality multigrade gas engine crankcase oil for all-season use in commercial vehicle engine operation fueled with compressed natural gas, liquified natural gas and liquified petroleum gas. The product is formulated with a low ash additive system to provide protection against wear and minimize the formation of sludge thereby contributing to overall engine cleanliness.

Special HD Gas Engine Oil 15W-40 meets the following performance requirements:
Cummins CES 20074, Cummins CES 20085, DDC 93K216, API CF-4 level.

APPLICATIONS

Recommended as a crankcase oil in natural and liquified gas alternative fueled engines in delivery trucks, metropolitan transit carriers, and other commercial vehicles.