



Relyant[®]

PREMIUM (R&O) TURBINE OILS ISO GRADES 150, 220, 320

ISO Grade	<u>Typical Properties</u>		
	150	220	320
Viscosity, cSt			
At 40 C	148	210	304
At 100 C	14	18	22.5
Viscosity Index	91	91	91
Flash Point, (COC)°F	465	475	485
Pour Point, °F	+15	+15	+15
Turbine Oil Stab. ASTM D-943	3000	2500	2500
Neut. No., TBN-C, ASTM 974	< 0.11	< 0.11	< 0.11
Gravity, API @ 60° F	28.0	27.0	26.5

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Premium-quality oils formulated from HVI paraffinic base stock with selected performance additives to meet the demanding characteristics of special industrial applications.

APPLICATIONS

Formulated to meet typical turbine oils properties and utilization where a high viscosity grade oil is necessary, i.e. gear cases, special bearing systems. These high viscosity premium turbine oils have excellent thermal/oxidation stability and anti-foam properties. These features together with excellent demulsibility and rust protection characteristics make them particularly well suited for multi-purpose industrial applications where higher ISO (grades) viscosities are required. Other applications include machine tools, speed reducers, roller chains, cone drives, helical gear reducers, large motor bearings, plain bearings, slow speed ball and roller bearings and crushers.