

HEAVY DUTY GAS ENGINE OIL

15W-40 MULTIGRADE

Product Description

Heavy Duty Gas Engine Oil is a premium-quality multigrade crankcase oil formulated for year-round use in commercial vehicles fueled with compressed natural gas (CNG), liquefied natural gas (LNG), or liquefied petroleum gas (LPG). It features a low ash additive system to protect against wear and minimize sludge formation, contributing to excellent engine cleanliness and long-term performance.

This formulation meets the following performance requirements: Cummins CES 20074, Cummins CES 20085, DDC 93K216, API CF-4

Applications

Recommended for use as a crankcase oil in commercial engines powered by natural or liquefied gas. Ideal for delivery trucks, transit carriers, and other commercial vehicles operating under demanding conditions.

Typical Properties

Property	15W-40
Viscosity @ 40°C (cSt)	113
Viscosity @ 100°C (cSt)	15.2
Viscosity Index	140
Viscosity CCS cP @ -20°C	6600
Flash Point °F (COC)	420
Pour Point °F	-25
Sulfated Ash % wt	0.50
Neutralization No. (TBN-E)	5.0
API Gravity @ 60°F	28.0

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process while others are not. All of them may vary within tolerable ranges.