

Low-Temp Premium Tractor Hydraulic Fluid

Relyant® Low-Temp Premium Tractor Hydraulic Fluid is a high-quality, specially designed lubricant containing anti-rust, anti-foam, and oxidation inhibitors, plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is a low viscosity type of oil that resists thickening in extreme cold weather. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition, while providing excellent protection against seal and pump deterioration.

Key Features & Benefits

- Exceptional low temperature fluidity for cold weather applications.
- Anti-wear, anti-rust, and anti-foam protection.
- Detergents to maintain system cleanliness and protect components.
- Excellent seal and pump protection under demanding conditions.
- Multipurpose formulation for transmissions, differentials, hydraulics, and power steering units.

Recommended Applications

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic and power steering units in various makes of tractors and farm equipment that require low viscosity and exceptional cold temperature performance. Suitable for applications where the following OEM fluids are specified: John Deere J20D, MS-1207/1209, JIC-144/145, Caterpillar TO-2, ABEX/Dennison HF-0, HF-1, HF-2 (pumps only), and Vickers 35VQ25.

Typical Properties

Property	Typical Value
SAE Grade	Automotive 0W-16 (Approx), Gear 75
Viscosity @ 40°C (cSt)	34.42
Viscosity @ 100°C (cSt)	7.1
Viscosity Index	175
Flash Point, °C (°F)	180 (356)
Pour Point, °C (°F)	-45 (-49)
Gravity, API @ 60°F	28.2
Density, lbs/gallon	7.38

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.