



# Relyant<sup>®</sup>

## EMD/TRANS ENGINE OIL MARINE & RAILROAD [HVI BASE + TBN 9]

### Typical Properties

SAE Grade		
Engine Class	30	40
Viscosity, cSt		
At 40 C	111	152
At 100 C	12.1	14.8
Viscosity Index	97	96
Flash Point, (COC) Deg F	435	450
Pour Point, Deg F (C)	-5(-21)	0(-18)
TBN, ASTM D 2896	9	9
Ash, %wt.-Sulfated	1.0	1.0
Zinc Content, ppm	<10	<10
Chlorine, ppm	<50	<50
Gravity, API @ 60 F	28.3	27.2
Density, lbs/gal @ 60F	7.373	7.124

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

Outstanding high-dispersancy with reserve alkalinity crankcase oil for railroad and marine diesel engines. Compounded from HVI Base (Paraffinic) Oils. Contains detergent, dispersant, anti-wear/EP agent, antioxidant, corrosion inhibitor, and foam-suppressant additives. The additive system does NOT contain 'zinc-compound' derivatives; they are classified as zinc-free at less than 10 ppm zinc in the formulated product; they are non-chlorinated.

### APPLICATIONS

Recommended for use in Electro-Motive Division of General Motors Corporation (EMD), Caterpillar, General Electric Generation IV, LMOA Generation V, VI, and other diesel engines operating on lower sulfur distillate-fuel with a sulfated ash of 1.0%. Meets API Service Classification Level "CD" and can be used in all two and four cycle, turbocharged and non-turbocharged, railroad diesel engines burning distillate type fuels where the use of a zinc-free additive system and HVI base oils are preferred. EMD and GE Engines manufactured for railroad and marine use are frequently used in stationary power generation systems with similar crankcase lubrication requirements.