



# Relyant

## HIGH PERFORMANCE 4-STROKE MOTOR CYCLE ENGINE OIL

### Typical Properties

	<u>5W-30</u>	<u>10W-30</u>	<u>10W-40</u>	<u>20W-40</u>	<u>20W-50</u>
Viscosity, cSt					
At 40 °C	63	68.5	95	145	160
At 100 °C	10.5	10.5	14	15	18.2
Viscosity Index	150	140	150	104	127
Flash Point, (COC) Deg F	410	415	425	420	430
Pour Point, Deg F	-35	-30	-25	-20	-15
Gravity, API °	35.0	31.1	31.1	29.3	28.7
Density, lb/gal @ 60 °F	7.17	7.26	7.26	7.33	7.36
Appearance	Amber	Amber	Amber	Amber	Amber

The values shown are typical of current production. Some are controlled in manufacturing process, while others are not. All of them may vary within tolerable ranges.

Relyant® High Performance 4-stroke Motorcycle Engine Oil is designed to help protect components inside motorcycle applications. This product has been carefully formulated with proprietary additives chosen for exceptional wear protection, sludge and garnish resistance, and thermal stability that performs exceptionally well in systems utilizing a wet clutch. Relyant High Performance 4-Stroke Motorcycle Engine Oil offers excellent rust and corrosion control, superior deposit control by cleaning existing deposits and help control sludge formation. It provides high temperatures film strength for optimum friction performance to help extending service life.

### APPLICATIONS

Relyant® High Performance 4-stroke Motorcycle Engine Oil can be used in 4-stroke motor cycle engines, including racing, high performance, street and off-road motorcycles. This product is suitable for use in applications calling for JASO MB type oils