



# ***Relyant***

## **High Performance 4-Stroke Water Cooled Engine oil**

### Typical Properties

	<u>10W-30</u>	<u>20W-40</u>	<u>25W-40</u>	<u>25W-50</u>
Viscosity, cSt				
At 40 °C	68.5	141.0	145.0	199.5
At 100 °C	10.5	15.1	15.0	19.3
Viscosity Index	140	108	104	110
Flash Point, (COC) Deg F	425	440	450	450
Pour Point, Deg F	-25	-15	-10	-10
Gravity, API °	31.5	28.5	27.6	27.0
Density, lb/gal @ 60 °F	7.23	7.36	7.41	7.43
Appearance	Amber	Amber	Amber	Amber
Phosphorous	760 ppm	760 ppm	760 ppm	760 pp.
TBN	8	8	8	8

The values shown are typical of current production. Some are controlled in manufacturing process, while others are not. All of them may vary within tolerable ranges.

Relyant® High Performance 4-stroke Water Cooled Engine Oil is designed to impart high lubricating performance in four-stroke gasoline marine engines. This product has been carefully formulated to provide wear protection and help increase catalyst life in newer inboards using catalytic converters. Relyant® High Performance 4-stroke Water Cooled Engine Oil is fortified with high quality base oils and special additives to provide excellent rust and corrosion control. This product offers superior deposit control by cleaning existing deposits and help control sludge formation.

### APPLICATIONS

Relyant® High Performance 4-stroke Water Cooled Engine Oil can be used in gasoline water cooled 4-stroke marine inboard, outboard, and sterndrive personal watercraft engines operating in severe fresh or salt marine environments. This product is suitable for use in applications calling for NMMA FC-W type oils.