



Relyant[®]

LOW-TEMP PREMIUM TRACTOR HYDRAULIC FLUID

Typical Properties

SAE Grade	
Automotive Gear75	OW-16 (Approx)
Viscosity, cSt	
At 40°C	34.42
At 100°C	7.1
Viscosity Index	175
Flash Point, Deg C/(F) (min)	180(356)
Pour Point, Deg C/(F)	-45(-49)
Gravity, API @ 60°F	28.2
Density, lbs/gallon	7.38

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.

A high quality, specially designed lubricant containing anti-rust, anti-foam and oxidation inhibitors; plus other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is a low viscosity type of oil that resists thickening in extreme cold weather. It is compounded with detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition; and provides excellent protection against seal and pump deterioration.

APPLICATIONS

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic and power steering units in many different makes of tractors and farm equipment that need low viscosity with exceptional cold temperature properties. Low-Temp Premium Tractor Hydraulic Fluid can be used for those hydraulic, wet brake, and transmission applications where the following OEM fluids are recommended: John Deere J20D, MS-1207/1209, JIC-144/145, Caterpillar TO-2, ABEX/Dennison HF-0, HF-1, HF-2(pumps only), and Vickers 35VQ25.