

Synthetic HD 0W-40, 5W-30, & 5W-40 Multigrade Heavy-Duty Motor Oil

For EGR, DPF, and DOC-Equipped Diesel Engines | Premium All-Season Synthetic Protection

Product Description

Synthetic HD 0W-40, 5W-30 and 5W-40 Multigrade Heavy-Duty Motor Oils are designed for exceptional year-round performance in demanding diesel engine applications. Formulated with premium synthetic base oils and a robust additive system, these multigrade lubricants meet the latest standards for high-performance diesel engines, including those equipped with EGR, DPF, and DOC emission control technologies. They offer outstanding cold-start fluidity, oxidation stability, wear protection, and soot control to extend engine life under severe service conditions.

Key Features & Benefits

- Advanced synthetic formulation supports extended drain intervals and high thermal stability.
- Outstanding protection under both cold-start and high-load operating conditions.
- Meets performance requirements for EGR, DPF, and DOC-equipped engines.
- High viscosity index ensures consistent lubrication across extreme temperatures.
- Suitable for both diesel and four-cycle gasoline engine applications.

Applications

- Recommended for heavy-duty diesel engines with advanced emission control systems.
- Ideal for mixed fleet service including highway, off-road, and industrial equipment.
- Formulated for engines requiring low-temperature fluidity and high-temperature stability.

Compatible with Ultra-Low Sulfur Diesel (ULSD) fuel environments

Typical Properties

| Property | 0W-40 | 5W-30 | 5W-40 |
|-----------------------------|-----------|---------|-----------|
| Viscosity, cSt @ 40°C | 83 | 69 | 104 |
| Viscosity, cSt @ 100°C | 14.3 | 11.4 | 15.0 |
| Viscosity Index | 180 | 159 | 176 |
| Viscosity, CCS @ -35°C (cP) | 5900 | | - |
| Viscosity, CCS @ -30°C (cP) | - | 6190 | 6498 |
| Flash Point, °C/°F | 210 / 410 | 227/440 | 227 / 440 |
| Pour Point, °C/°F | -45 / -49 | -40/-40 | -40 / -40 |
| Sulfated Ash, %wt | 1.0 | 1.0 | 1.0 |
| TBN (Neutralization No.) | 9.0 | 1.0 | 9.0 |
| API Gravity @ 60°F | 34.3 | 1.0 | 32.5 |

^{*}The values shown are typical of current production. Some are controlled in the manufacturing process while others are not. All of them may vary within tolerable ranges.