

Light Duty Long Life Orange Antifreeze/Coolant Pre-Mix 50/50

Product Overview

Relyant® Long Life Orange antifreeze/coolant is a universal product that contains no Nitrites, Silicates, Borates, or Amines. It is specially formulated with high quality industry-leading additives and is the perfect choice in all vehicles requiring DEX-COOL® (GM 6277M or GMW 3420) coolant. Relyant® Premium Long Life Orange provides optimum protection against:

- Freeze-up
- Boil Over
- Scale Build-up
- Clogging
- Sludge
- Rust/Corrosion

Advantages

- Meets or exceeds Light Duty ASTM D-3306 and SAE J1043.
- 5 year or 150,000 mil service interval with flush and fill.
- Blended with pure deionized water for your quality needs.
- Long term corrosion protection for all system metals.
- No silicate dropout or gelling during storage or use.
- Full Organic Acid Technology (OAT)
- For safety- All Relyant® Antifreeze contains a bittering agent.

Specifications

Will provide outstanding performance in the following applications:

- ASTM D-3306
- Ford WSS-M97B44-D
- SAE J1941
- BMW
- Honda
- Subaru
- SAE J1034
- Ford WSS M97B44-D2
- Toyota
- Mitsubishi
- GM 6277M
- Volvo
- GMW 3420
- Volkswagen
- SAE J814

Typical Properties

Description	Typical Values	Test Method
Appearance	Visual	Orange
Specific Gravity @ 60°F	1.053-1.083	D-1122
Freeze Point, at 50% max	-34°F	D-3321
pH at 50% Solution	8.5-10.0	D-1287
Reserve Alkalinity min.	4	D-1121
Foam Test	150 ml/5 sec	D-1881

BOIL OVER PROTECTION			
Type of Coolant Test	Atmospheric pressure	14 LB cap	15 LB cap
Coolant Boiling	224°F	262°F	265°F
Coolant Freezing	-34°F	-34°F	-34°F

*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.