



### SYNTHETIC TRACTOR HYDRAULIC FLUID WB

#### Product Description

Relyant® Synthetic Tractor Hydraulic Fluid WB is a full synthetic base lubricant formulated with an additive system containing anti-rust, anti-foam, oxidation inhibitors and other additives necessary for the wide range of applications recommended by various tractor manufacturers. The product is an "all-seasonal" type of fluid with a wide temperature/viscosity range that imparts thickening resistance in cold weather and thinning in the heat of summer. It is compounded with dispersant/detergents to keep transmissions clean and maintain hydraulic control circuits in perfect working condition. The product further provides excellent protection against seal and pump deterioration. Operators, especially farmers, will appreciate the multi-purpose application of Synthetic Tractor Hydraulic Fluid WB, with equipment employing a central reservoir, lubricating transmissions, final drives, and various hydraulic systems of tractors.

#### APPLICATIONS

Formulated and recommended for multipurpose use in transmissions, differentials, hydraulic and power steering units in many different makes of tractors and farm equipment. Synthetic Tractor Hydraulic Fluid WB is suitable for use in the following applications: John Deere JDM J20D, White Farm Q1826, Volvo WB-101/97303, WB 102/97304

#### Typical Properties

SAE Grade Automotive	75W-80
Viscosity, cSt At 40°C	39.4
Viscosity, cSt At 100°C	7.6
Viscosity Index	167
Flash Point, Deg C/(F) (min)	218(425)
Pour Point, Deg C/(F)	-45(-49)
Gravity, API @ 60°F	33.4
Density, lbs/gallon	7.15

The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges